



4-Port VGA Splitter Model: MT-1304

MT-1304 video splitter provides video input signals to 4 video outputs each at 130 MHz after duplication. Users can boost video signals from the video gain knob within a transfer range up to 45m.



Features:

- 1) One video input to 4 video outputs.
- 2) RGB: Bandwidth 130MHz
- 3) Long distance transmission - up to 45m.
- 4) High video resolution - up to 1600 x 1280.
- 5) DDC, DDC2, DDC2B Compatible (Port 1 only).
- 6) Supports VGA, XGA, SVGA, UXGA & multisync monitors
- 7) OS Support: Windows 2000, Windows XP, Linux, Mac & Sun
- 8) Power: AC 220V 50/60Hz 5W
- 9) Input level: 0.5-1VP-P
- 10) Input Resistance: 75Ω
- 11) HV Channel: Input Level 0.7-5Vp-p
- 12) Enclosure: Metal

Specifications:

Display Connections		4
Connectors	Video In	1 x HDB-15 Male (Blue)
	Video Out	2 x HDB-15 Female (Blue)
	Power	1 x DC Jack (Black)
Switches	Video Gain	1 x Knob
LEDs	Power	1
Video Bandwidth		130 MHz
Video		1600*1280 @ 60Hz
Signal Range		Up to 45m (210')
Power Consumption		DC9V, 1.89W (Max.)
Environment	Operating Temp.	0-50°C
	Storage Temp.	-20-60°C
	Humidity	0-80% RH, Non-condensing
Physical Properties	Housing	Metal
	Weight	379G
	Dimensions (L x W x H)	

Made in China