

IGBT MODULE (P-Series)

■ Features


- Square SC SOA at $10 \times I_C$
- Simplified Parallel Connection
- Narrow Distribution of Characteristics
- High Short Circuit Withstand-Capability



■ Applications

- High Power Switching
- A.C. Motor Controls
- D.C. Motor Controls
- Uninterruptible Power Supply

■ Outline Drawing




■ Maximum Ratings and Characteristics

• Absolute Maximum Ratings ($T_c=25^\circ\text{C}$)

Items		Symbols	Ratings	Units
Collector-Emitter Voltage		V_{CES}	1400	V
Gate -Emitter Voltage		V_{GES}	± 20	V
Collector Current	Continuous $T_c=25^\circ\text{C}$	I_C	150	A
	Continuous $T_c=80^\circ\text{C}$		100	
	1ms $T_c=25^\circ\text{C}$	$I_C \text{ PULSE}$	300	
	1ms $T_c=80^\circ\text{C}$		200	
	1ms	$-I_C$	100	
Max. Power Dissipation		P_C	780	W
Operating Temperature		T_j	+150	$^\circ\text{C}$
Storage Temperature		T_{stg}	-40 ~ +125	$^\circ\text{C}$
Isolation Voltage	A.C. 1min.	V_{is}	2500	V
Screw Torque		Mounting *1	3.5	Nm
		Terminals *2	3.5	

Note: *1:Recommendable Value; 2.5 ~ 3.5 Nm (M5)

■ Equivalent Circuit



• Electrical Characteristics (at $T_j=25^\circ\text{C}$)

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Zero Gate Voltage Collector Current	I_{CES}	$V_{GE}=0V$ $V_{CE}=1400V$			2.0	mA
Gate-Emitter Leakage Current	I_{GES}	$V_{CE}=0V$ $V_{GE}=\pm 20V$			400	μA
Gate-Emitter Threshold Voltage	$V_{GE(th)}$	$V_{GE}=20V$ $I_C=100mA$	6.0	8.0	9.0	V
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$	$T_j=25^\circ\text{C}$ $V_{GE}=15V$ $I_C=100A$		2.7	3.0	V
		$T_j=125^\circ\text{C}$ $V_{GE}=15V$ $I_C=100A$		3.3		
Input capacitance	C_{ies}	$V_{GE}=0V$		10000		pF
Output capacitance	C_{oes}	$V_{CE}=10V$		1500		
Reverse Transfer capacitance	C_{res}	$f=1MHz$		650		
Turn-on Time	t_{ON}	$V_{CC}=600V$			1.2	μs
	t_r	$I_C=100A$			0.6	
Turn-off Time	t_{OFF}	$V_{GE}=\pm 15V$			1.0	
	t_f	$R_G=9.1\Omega$			0.3	
Diode Forward On-Voltage	V_F	$I_F=100A$ $V_{GE}=0V$		2.4	3.3	V
Reverse Recovery Time	t_{rr}	$I_F=100A$			350	ns

• Thermal Characteristics

Items	Symbols	Test Conditions	Min.	Typ.	Max.	Units
Thermal Resistance	$R_{th(j-c)}$	IGBT			0.16	$^\circ\text{C/W}$
	$R_{th(j-e)}$	Diode			0.33	
	$R_{th(c-f)}$	With Thermal Compound		0.025		