





CP3-12

PHYSICAL SPECIFICATION

Nominal Voltage		12V
Nominal Capacity (20HR)		3Ah
Dimension	Length	70±1mm (2.76 inches)
	Width	47±1mm (1.85 inches)
	Container Height	100±1mm (3.94 inches)
	Total Height	105±1mm (4.13 inches)
Weight		Approx. 0.59Kg (1.30lbs)
Standard Terminal		Fasten Tab No.187E



F1(Fasten Tab No.187E)
Standard Terminal




ELECTRICAL SPECIFICATION

Characteristics

Capacity	20 hour rate (0.15A)	3Ah
	10 hour rate (0.27A)	2.8Ah
	5 hour rate (0.51A)	2.6Ah
	3 hour rate (0.75A)	2.2Ah
	1hour rate (1.8A)	1.8Ah
Capacity affected by temperature	40℃ (104 °F)	102%
	25℃ (77 °F)	100%
	0℃ (32 °F)	85%
Internal Resistance		Full charged battery (25℃,77 °F) 25mΩ
Constant Voltage Charge	Cycle	Initial Charging Current less than 0.9A Voltage 7.20~7.50V at 25℃ (77 °F) Temperature Coefficient -15mV/℃
	Standby	No limit on Initial Charging Current Voltage 6.75~6.90V at 25℃ (77 °F) Temperature Coefficient -10mV/℃

Discharge curves @ 25℃ (77 ° F)



Made in China