


VISTA


CP7-12(5.5Ah)

PHYSICAL SPECIFICATION

Nominal Voltage		12V
Nominal Capacity (20HR)		5.5Ah
Dimension	Length	151±1mm (5.94 inches)
	Width	65±1mm (2.56 inches)
	Container Height	95±1mm (3.74 inches)
	Total Height	100±1mm (3.94 inches)
Weight		Approx. 1.72Kg (3.79lbs)
Standard Terminal		Fasten Tab No.187E



F1(Fasten Tab No.187E)
Standard Terminal




ELECTRICAL SPECIFICATION

Characteristics

Capacity		20 hour rate (0.275A) 10 hour rate (0.495A) 5 hour rate (0.935A) 3 hour rate (1.375A) 1hour rate (3.3A)	5.5Ah 5.2Ah 4.7Ah 4.1Ah 3.3Ah
Capacity affected by temperature		40℃ (104 °F) 25℃ (77 °F) 0℃ (32 °F)	102% 100% 85%
Internal Resistance		Full charged battery (25℃,77 °F) 25mΩ	
Constant Voltage Charge	Cycle	Initial Charging Current less than 1.6A Voltage 14.4~15.0V at 25℃ (77 °F) Temperature Coefficient -30mV/℃	
	Standby	No limit on Initial Charging Current Voltage 13.5~13.8V at 25℃ (77 °F) Temperature Coefficient -20mV/℃	

Discharge curves @ 25℃ (77 ° F)



Made in China