



8-Port 10M Ethernet Hub Model: TEH8809



Description:

TEH8809 is an 8 10M hub. The tabletop mini models with the shell structural, suitable for the middle and small scale work network, port speed 10M; Provides the cascade port UPLINK convenience network to expand accommodates; auto-isolate the mistaken ports to guarantee the normal operation of network.. Belongs to the shared network equipment, the main function is the signal receives carries on the regenerative amplification, broadcasts to each port which connected in, expands network transmitting range.

Features:

- Compatible with IEEE802.3 10BASE-T standard
- Provide 5 pieces 10M RJ-45 interfaces
- Provide 1 Uplink port to use in the straight line of flux cascade
- Uses CSMA/ CD protocol, star topology
- Complete LEDS indicators, simplify the breakdown and indicates the HUB active situation
- The mini plastic housing tabletop, specialized built-out power supply

Specifications:

Model	TEH8809
Network Standard	IEEE802.3u 100BASE-TX
Protocol	CSMA/CD
Topology	Star(can be used to Mail Line)
Support wire type	10Base-T: 3, 4 or 5 kinds of shields/Non-shielded twisted pair, maximum transmitting range:100 meters
Power Supply	Built-out power supply adapter (DC:7.5V 1A)
Working surrounding	Temperature: 0° to 80°C Humidity: 5%~95% without condensation

Made in China