

UPS C3KVA ON-LINE



Specifications:

Model		C3KVA
Rated Power	VA/W	3KVA/2100W
INPUT	Normal Voltage Range	220VAC
	Voltage Range	115 ~300VAC
	Frequency Range	46 ~54Hz
	Power Factor	0.97
	Connector	Hardwired
OUTPUT	Voltage	220VAC $\pm$ 2%
	Frequency	50Hz $\pm$ 0.1% (Battery Mode)
	Waveform	Sine Wave
	Power Factor	0.7
	Voltage Distortion	4%
	Overload Capability	108%~150% for 30 sec., 150% for 300ms
	Current Crest Ratio	3:1 max.
	Connection	Hardwired
Battery	Type	Sealed,Maintenance free,Lead-Acid
	Capacity	12v x 8pcs =96v
	Back up Time	Depends on the capacity of the external battery bank
Transfer Time	0ms	
Maintenance Bypass Switch	Yes	
LED indicators	Status	Load level/Battery level,Battery,Utility power ,Inverter,Bypass,Overload, Fault.
Audible Alarm	Bypass	Alarm beeps every two minutes
	Battery Discharge	Alarm beeps every four seconds ,every second if battery low
	Overload	Alarm beeps two for every second
	Fault	Alarm beeps continuously
Acoustic Noise	At 1 meter distance	50 dBA
Communications	RS232 serial interface	
Parallel Port	Up to three units in parallel for power redundancy and load sharing	
Environmental	Operating Temperature	0 ~40°C
	Operating Humidity	20%~90% non-condensing
Weight	Net Weight (KG)	16
	Gross Weight (KG)	17
Dimension	Unit Size(mm)	450*190*330