

FLUKE.

Digital Multimeter Model: 77 IV

Features: -

- 1 Large display
- 2- Backlight for work in dim areas
- 3- Min / Max to record signal fluctuations
- 4- Ergonomic overmolded housing with integrated probe holders
- 5- Free your hands with the optional TPAK magnetic hanger
- 6- Auto and Manual ranging
- 7- Meets Measurement Category 1000 V CAT III and Category IV 600 V safety standards



Specifications:

Voltage DC	Range: 6.000V - 1000V Best Accuracy: +/- (0.3% + 1) Best Resolution: 0.1 mV
Voltage AC	Range: 600.0 mV-1000V Best Accuracy: +/- (2.0% + 2) Best Resolution: 1.0 mV
Amps AC	Range: 60.00 mA – 10A Best Accuracy: +/- (1.5% + 2) Best Resolution: 0.01mA
Amps DC	Range: 60.00 mA – 10A Best Accuracy: +/- (2.5% + 2) Best Resolution: 0.01 mA
Resistance	Range: 600.0 ? - 50 M? Best Accuracy: +/- (0.5% + 1) Best Resolution: 0.1?
Capacitance	Range: 1nF- 9,999 µF Best Accuracy: +/- (1.2% + 2) Best Resolution: 1 nF
Frequency	Range: 99.99Hz- 99.99kHz Best Accuracy: +/- (0.1% + 1) Best Resolution: 0.01Hz
Safety	ANSI/ISA S82.02.01, CSA C22.2-1010.1, IEC 61010 to 1000 V Measurement Category III, 600 V Measurement Category IV
Certifications	CSA, TÜV (EN61010), UL, Π, ; (N10140),VDE

Made in U.S.A.