



Digital Multimeter Model: CD771

Features:

- 3-3/4 digits 4000 count
- Data hold, Range hold, Relative function
- Continuity buzzer with LED indication, Diode test
- Auto power off function (30min.)

Standard Accessories Included:

- Test leads (TL-23) x 1set

Specifications:



Function	Measuring range	Best accuracy	Resolution	Input impedance	
DCV	400m/4/40/400/1000V	± (0.5%+2)	0.1mV	10M~	
ACV	4/40/400/1000V	± (1.2%+7)	1mV	100MΩ	
DCA	400μ/4000μ/40m/400m/4/10A	± (1.4%+3)	0.1μ		
ACA	400μ/4000μ/40m/400m/4/10A	± (1.8%+5)	0.1μ		
Resistance	400/4k/40k/400k/4M/40MΩ	± (1.2%+5)	0.1Ω		
Capacitance	50n/500n/5μ/50μ/100μF	± (5%+10)	0.01nF		
Frequency	5/50/500/5k/50k/100kHz	± (0.3%+3)	0.001Hz		
Continuity	Buzzer sounds and LED lights up at between 0Ω and 85Ω (±45Ω) . Open voltage: approx. 0.4V				
Diode test	Open voltage: approx. 1.5V				
Battery check	Approximate value (30Ω load) 1.5V battery only				
Bandwidth	40~400Hz (sine wave)				
Fuse / Battery	0.5A/1000V 30kA Φ6.35X32mm 10A/1000V 30kA Φ10X38mm	R6P×2			
Size / Weight	H166XW82XD44mm/360g				
Standard accessories included	Test lead (TL-23) , Instruction manual				

Made in Japan