

Analog multitester

Model: YX360TRF

Description:

- 1- Drop shock-proof meter
- 2- Null (zero center) meter $\pm 5/\pm 25$ in DCV
- 3- High resistance up to 200M ohm with low voltage
- 4- Protective full-face cover
- 5- Capacitance, dB, Li measurement

Standard Accessory:

Hand strap

Optional Accessories:

DC high voltage probe (HV-10T)

hFE probe (HFE-6T)



Measurement range:

DCV	0.1/0.25/2.5/10/50/250/1000V
ACV	10/50/250/750V
DCA	50 μ /2.5m/25m/0.25A
Ω	2k/20k/200k/2M/200M Ω
C	10 μ F
dB	10dB --- +22dB (for 10VAC) --- + 62dB
Li	0 ~ 150mA at x 1 range 0 ~ 15mA at x 10 range 0 ~ 1.5mA at x 100 range 0 ~ 150 μ A at x 1k range 0 ~ 1.5 μ A at x 100k range

Features:

Meter structure	Taut-band type (Drop shock proof)
Zero center function	Yes
Range selection	Manual
Bandwidth	300kHz ~ 100kHz (AC 10V)
Withstand voltage	3kV AC (1 min.) between input terminal and case

General specifications:

Accuracy temperature	23°C $\pm$ 2°C 45 ~ 75% RH No condensation
Operating temperature	0°C ~ 40°C 45 ~ 75% RH No condensation
Power supply	R6 (IEC) or UM-3 (1.5V) x 2
Fuse protection	0.5A/250V 5.2mm x 20mm
Dimension	159.5(H) x 129(W) x 41.5(D) mm
Weight	Approx. 320g
CE mark	Yes
Safety	CAT III for 600V DC&AC CAT II for 1000V DC CAT II for 750V AC