

SM-7030

DMM WITH LCD & POINTER DISPLAY



- 3 1/2 digits LCD & pointer dual display showing both static and dynamic inputs
- Newly design housing, easy to hold in either hand
- Continuity test with buzzer
- Auto polarity switching
- Full range protection
- Conforms to IEC1010 CAT.II 600V

Technical specifications

DCV: 200m/2/20/200/600V (10M Ω /V),
 $\pm 0.5\% + 2\text{dgt}$, $\pm 3\%$ F.S.

ACV: 200m/2/20/200/600V,
 $\pm 0.8\% + 3\text{dgt}$, $\pm 4\%$ F.S.

DCA: 200 μ /2m/20m/200m/10A,
 $\pm 1.0\% + 3\text{dgt}$, $\pm 3\%$ F.S.

ACA: 200 μ /2m/20m/200m/10A,
 $\pm 1.5\% + 3\text{dgt}$, $\pm 4\%$ F.S.

OHM: 20/200/2k/20k/200k/2M/20M Ω ,
 $\pm 0.8\% + 3\text{dgt}$, $\pm 3\%$ F.S.

BATT test: 1.5V(100mA), 9V(10mA)

Audible continuity: $< 30\Omega$

Diode test: 2.4V/1mA

Dimensions: 108x190x50mm, ~470g

Battery: 9Vx1(6F22)

Accessories: holster

REF: 027030X1200

☒ CE (EMC), ☐ UL, ☐ CE (LVD)

inometer