

CLAMP METER KYORITSU 2055



- Designed to meet international safety standard IEC 61010-1 CAT IV 600V.
- CAT IV Clamp Meters can measure the Voltage and Current in both every low and high power circuits.

- Very useful for power distribution companies, power utilities and maintenance fields.

AC A	0 - 600.0/1000A
	±1.5%rdg±5dgt (50/60Hz)
	±3.0%rdg±5dgt (40 - 400Hz)
DC A	0 - 600.0/1000A
	±1.5%rdg±5dgt
AC V	6/60/600V
	Auto Ranging
	±1.3%rdg±4dgt (50/60Hz)
	±3.0%rdg±5dgt (40 - 400Hz)
DC V	600m/6/60/600V
	Auto Ranging
	±1.0%rdg±3dgt
Ω	600/6k/60k/600k/6M/60M Ω (Auto Ranging)
	±1%rdg±5dgt (600 - 6M) / ±5%rdg±8dgt (60M)
Continuity buzzer	Buzzer Sounds at 100 Ω
Frequency/DUTY	10/100/1k/10kHz (Auto Ranging) / 0.1 - 99.9%
Conductor size	Ø40mm
Safety Standard	IEC 61010-1 CAT IV 600V,
	IEC 61010-031,
	IEC 61010-2-032,
	IEC 61326
Power source	R03 (1.5V) (AAA) × 2
Dimensions	254(L) × 82(W) × 36(D)mm
Weight	310g
Included Accessories	7066A (Test leads)
	9094 (Carrying case)
	Instruction Manual

