

CLAMP METER UNI-T UT208A



Specifications	Range	Best Accuracy
Model		UT208A
AC Current (A)	40A/400A/1000A	$\pm(2\%+2)$
DC Current (A)	40A/400A/1000A	$\pm(1.5\%+5)$
AC Voltage (V)	400mV/4V/40V/400V/750V	$\pm(1.2\%+3)$
DC Voltage (V)	400mV/4V/40V/400V/1000V	$\pm(0.8\%+1)$
Resistance (Ω)	400 Ω /4K Ω /40K Ω /400K Ω /4M Ω /40M Ω	$\pm(1\%+2)$
Frequency (Hz)	10Hz/100Hz/1KHz/10KHz/1MHz/10MHz	$\pm(0.1\%+3)$
Capacitance (F)	4nF/40nF/400nF/4 μ F/40 μ F/100 μ F	$\pm(4\%+3)$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C ~ 1000 $^{\circ}$ C	$\pm(2.5\%+3)$
Features		
Display Count		4000
Auto Range		√
Jaw Capacity		55mm
LCD Backlight		
Diode		√
Data Hold		√
Duty Cycle	0.1%~99.9%	√
Auto Power Off		√
Continuity Buzzer		√
Low Battery Indication		√
Full Icon Display		√



0988109283

Input Impedance for DCV	$\geq 10\text{M}\Omega$	√
General Characteristics		
Power	9V Batteries (6F22)	
LCD Size	47mm X 30mm	
Product Color	Red and Grey	
Product Net Weight	533g	
Product Size	286mm X 105mm X 45mm	
Standard Accessories	Batteries, Test Lead, Tool Box	
Standard Individual Packing	Gift Box, Carrying Bag, English Manual	
Standard Quantity Per Carton	20pcs	
Standard Carton Measurement	600mm X 370mm X 474mm	
Standard Carton Gross Weight	28.3kg	