

CLAMP METER UNI-T UT210D



Specifications	Range	Best Accuracy
Model		UT210D
AC Current (A)	20A/200A	$\pm (2.5\%+8)$
DC Current (A)	20A/200A	$\pm (2\%+3)$
AC Voltage (V)	2V/20V200V/600V	$\pm (1\%+3)$
DC Voltage (V)	200mV/2V/20V200V/600V	$\pm (0.7\%+3)$
Resistance (Ω)	200 Ω /2K Ω /20K Ω /200K Ω /2M Ω /20M Ω	$\pm (1\%+2)$
Frequency (Hz)	10Hz/100Hz/1kHz/10kHz/60kHz	$\pm (0.1\%+4)$
Capacitance (F)	2nF/20nF/200nF/2 μ F/20 μ F/200 μ F/2mF/20mF	$\pm (4\%+5)$
Temperature ($^{\circ}$ C)	-40 $^{\circ}$ C ~ 1000 $^{\circ}$ C	$\pm(1\%+3)$
Temperature ($^{\circ}$ F)	-40 $^{\circ}$ F ~ 1832 $^{\circ}$ F	$\pm(1.5\%+5)$
Features		
Display Count		2000
Auto Range		$\checkmark$
Jaw Capacity		17mm
True RMS		$\checkmark$
Diode	Around 3.0V	$\checkmark$
NCV		$\checkmark$
Data Hold		$\checkmark$
Zero Mode		$\checkmark$
LCD Backlight		$\checkmark$
Auto Power Off	Around 15 Minutes	$\checkmark$

Continuity Buzzer		√
Low Battery Indication	≤2.5V	√
Input Protection		√
Input Impedance for DCV	≥10MΩ	√
General Characteristic		
Power	AAA 1.5V × 2	
LCD Size	39.3mm × 26.5 mm	
Product Color	Red and Grey	
Product Net Weight	170g	
Product Size	175mm × 60mm × 33.5mm	
Standard Accessories	Batteries, Test Lead, Point Contact Temperature Probe	
Standard Individual Packing	Box, Carrying bag, English Manual	
Standard Quantity Per Carton	40PCs	
Standard Carton Measurement	385mm×345mm×305mm (0.041 CBM Per Standard Carton)	
Standard Carton Gross Weight	11Kg	