

DMM KYORITSU 1009



- Display : 4000 counts.
- Auto range and manual range selector provided.
(with range hold feature)
- Resistance range provides audible continuity test.
- Automatically turns power off in about 30 minutes to conserve battery life.

- Direct current measurement up to 10A AC and DC.
- With Holster.

DC V	400mV/4/40/400/600V (Input Impedance 10M Ω) $\pm 0.6\%rdg \pm 4dgt$ (400mV/4/40/400V) $\pm 1.0\%rdg \pm 4dgt$ (600V)
AC V	400mV/4/40/400/600V (Input Impedance 10M Ω) $\pm 1.6\%rdg \pm 4dgt$ (20 - 400mV) $\pm 1.3\%rdg \pm 4dgt$ (4/40V) $\pm 1.6\%rdg \pm 4dgt$ (400/600V)
DC A	400/4000 μ A/40/400mA/4/10A $\pm 2.0\%rdg \pm 4dgt$
	(400/4000 μ A) $\pm 1.0\%rdg \pm 4dgt$
	(40/400mA) $\pm 1.6\%rdg \pm 4dgt$ (4/10A)
AC A	400/4000 μ A/40/400mA/4/10A $\pm 2.6\%rdg \pm 4dgt$
	(400/4000 μ A) $\pm 2.0\%rdg \pm 4dgt$
	(40/400mA/4/10A)
Ω	400 Ω /4/40/400k Ω /4/40M Ω $\pm 1.0\%rdg \pm 4dgt$ (400 Ω /4/40/400k Ω /4M Ω) $\pm 2.0\%rdg \pm 4dgt$ (40M Ω)
Continuity buzzer	400 Ω (Buzzer sounds below 100 Ω)
Diode test	1.5V Release Voltage: Approx. 0.4mA Test Current
Capacitance	40/400nF/4/40/100 μ F

Frequency	5.12/51.2/512Hz/5.12/51.2/512kHz/5.12/10MHz
DUTY	0.1 - 99.9% (Pulse width/Pulse period) $\pm 2.5\% \pm 5\text{dgt}$
Applicable standards	IEC 61010-1 CAT III 300V
	IEC 61010-2-031
	IEC 61326
Power source	R6 (1.5V) $\times 2$
Dimensions	161(L) $\times$ 82(W) $\times$ 50(D)mm
Weight	Approx. 280g
Included Accessories	7066A (Test leads)
	8919 (Ceramic fuse [10A/600V]) $\times 1$
	8923 (Fuse [0.5A/600V]) $\times 1$
	R6 $\times 2$
	Instruction Manual
Optional Accessories	7234 (Crocodile clip test lead)
	9095 (Carrying case)