

UNI-T UT120C



Main Features:

- Compact and slim
- Auto ranging
- Capacitance, frequency & duty cycle
- Data hold and relative mode
- Auto shut-off
- CAT-II rated
- Size: 4.3" x 2.3" x 0.4"
- Weight: 2.7oz

Included:

1. Test leads (hardwired)
2. 3V battery (CR2032)
3. Case
4. Instruction booklet

Specifications:

RANGE		ACCURACY	RESOLUTION
DC voltage	400mV / 600V	$\pm(0.8\%+3)$ @ 4V-400V	0.1mV-1V
AC voltage	400mV / 600V	$\pm(1.2\%+3)$ @ 4V-400V	1mV-1V
DC current	400 μ A / 400mA	$\pm(1.0\%+3)$ @ 400 μ A-4000 μ A	0.1 μ A-100 μ A
AC current	400 μ A / 400mA	$\pm(1.5\%+5)$ @ 40mA-400mA	0.1 μ A-100 μ A
Resistance	400 Ω / 40M Ω	$\pm(1.0\%+2)$ @ 4k Ω -400k Ω	0.1 Ω -10k Ω
Capacitance	4nF / 100 μ F	$\pm(4.0\%+3)$ @ 40nF-40 μ F	0.001nF-0.1 μ F
Frequency	10Hz / 100kHz	$\pm(0.5\%+3)$	0.1Hz-0.1kHz
Duty cycle	0.1% to 99.9%	$\pm(0.1\%)$	
Diode check	1.5V		
Low battery	<2.4V		