

UNI-T UT33A+



Main features:

1. Clear LCD display
2. Equipped with comfortable protective cover, test lead hanging slot
3. 2m drop proof with precision protection
4. Auto power off
5. Auto backlight off
6. Loud buzzer
7. Ergonomically designed rotary switch

Specifications	Range	Accuracy
		UT33A+
DC voltage (V)	200.0mV ~ 600V	$\pm(0.5\% + 3)$
AC voltage (V)	200.0mV ~ 600V	$\pm(0.7\%+3)$
	200.0V ~ 600V	
DC current (A)	200.0 μ A ~ 10.00A	$\pm(1.0\%+3)$
AC current (A)	200.0 μ A ~ 10.00A	$\pm(1.2\%+3)$
Resistance (Ω)	200.0 Ω ~ 200.0M Ω	$\pm(1.0\%+2)$
	200.0 Ω ~ 20.00M Ω	
Capacitance (F)	2.000nF ~ 2.000mF	$\pm(3\%+5)$
Features		
Max display		1999
Auto power off		√
Auto backlight off		√
Diode test		√
Continuity buzzer		√
Drop test		2m
Test probe holder		√
Safety rating		CAT II 600V
Range selection		Auto



0988109283

Battery test		
Temperature (°C/°F)		
NCV		
General Characteristics		
Power	AAA battery (zn-mn) 1.5V×2	
LCD size	66mm*51mm	
Product color	Red and grey	
Product net weight	473g	
Product size	131mm×95mm×58mm	
Standard accessories	Test lead, manual	
Standard individual packing	Gift box, manual	
Standard quantity per carton	60pcs	
Standard carton measurement	640mm×310mm×350mm	