

KYORITSU 3025A



- Short-Circuit Current up to 1.5mA
- Diagnosis Function of PI and DAR
- Newly-designed alligator clip
- It comes with a tough hard case
- Filter function reduces noise interference for obtaining

stable measurement

- Large display with Bar Graph indication and backlight
- Live voltage warning
- Safety standard IEC 61010-1 CAT IV 300V / CAT III 600V

(Photo: 3125A)

Rated voltage		250V	500V	1000V	2500V
Accuracy		0.0 - 100.0MΩ	0.0 - 99.9MΩ	0.0 - 99.9MΩ	0.0 - 99.9MΩ
			80 - 1000M Ω	80 - 999MΩ	80 - 999MΩ
				0.80 - 2.00G Ω	0.80 - 9.99GΩ
					8.0 - 100.0GΩ
		±5%rdg±3dgt	±5%rdg±3dgt	±5%rdg±3dgt	±5%rdg±3dgt
Short circuit current		1.5mA			
Output voltage					
	Accuracy	±10%	-10.2	0 - +20%	
	Monitor	±10%rdg±20V			

Voltage measurement

Measuring range	AC: 30 - 600V (50/60Hz), DC: $\pm 30 - \pm 600 \text{V}$
Accuracy	$\pm 2\% \text{rdg} \pm 3 \text{dgt}$

General

Applicable standards	IEC 61010-1, 61010-2-030 CAT IV 300V / CAT III 600V Pollution degree 2,
	IEC 61010-031, IEC 61326-1, 2-2
Power source	DC12V : LR14/R14 × 8pcs
Dimensions	177 (L) × 226 (W) × 100 (D) mm
	300 (L) × 315 (W) × 125 (D) mm (Hard case)
Weight	3025A: 1.7kg approx. (including batteries)
	4kg approx. (including accessories)
Included Accessories	7165A (Line probe: 3m), 7264 (Earth cord: 3m), 7265 (Guard cord: 3m),
	8019 (Hook type prod), 9180 (3025A Hard case), 9181 (3125A Hard case),
	LR14 (Alkaline battery size C) × 8, Instruction manual