


SONGLE RELAY



RELAY ISO9002

SRS/SRSZ



1. MAIN FEATURES

- ☐ Subminiature Type.
- ☐ Silver or Silver Alloy Contacts with Gold Plated.
- ☐ Low Dissipation.
- ☐ Sealed Type Available.
- ☐ Design conforms to foreign safety standard UL, CUL, TUV

2. APPLICATIONS

Microprocessor Control, Store Program Exchanger and Household Appliance.

3. ORDERING INFORMATION

SRS/SRSZ	XX VDC	S	L
Model of relay	Nominal coil voltage	Structure	Coil sensitivity
SRS/SRSZ	03 D5 D6 D9 12 24VDC	S: Sealed type	H: 0.20W
		F: Flux free type	L: 0.36W
			D: 0.45W


4. RATING

UL /CUL FILE NUMBER: E167996 1A/120VAC 24VDC
 TUV FILE NUMBER: R50056114 3A/250VAC 30VDC
 3A/120VAC 24VDC

5. DIMENSION (unit:mm)

DRILLING (unit:mm)

WIRING DIAGRAM



6. COIL DATA CHART (AT20 ° C)

Coil Sensitivity	Coil Voltage Code	Nominal Voltage (VDC)	Nominal Current (mA)	Coil Resistance (Ω) □	Power Consumption (W)	Pull-In Voltage (VDC)	Drop-Out Voltage (VDC)	Max-Allowable Voltage (VDC)
SRS(Z) (High Sensitivity)				10%	abt. 0.2 W	75% Max.	5% Min.	110%
	03	03	66.7	45				
	05	05	40	125				
	06	06	33.3	180				
	09	09	22.2	405				
	12	12	16.7	720				
SRS(Z) (Standard)	24	24	8.3	2880	abt. 0.36W	75% Max.	5% Min.	110%
	03	03	120	25				
	05	05	66.7	75				
	06	06	60	100				
	09	09	40.9	220				
	12	12	30	400				
SRS(Z) (Normal Sensitivity)	24	24	15	1600	abt. 0.45W	75% Max.	5% Min.	110%
	03	03	150	20				
	05	05	89.3	56				
	06	06	75	80				
	09	09	50	180				
	12	12	37.5	320				
	24	24	18.75	1280				

7. CONTACT RATING

Type	SRS/SRSZ	SRS/SRSZ
Item	1 Amp type	1 Amp type
Contact Capacity	Coil=0.2W	Coil=0.2W
Resistive Load (cosΦ=1)	1A 125VAC 1A 30VDC	3A 250VAC 1A 30VDC
Inductive Load (cosΦ=0.4 L/R=7msec)	0.3A 125VAC 0.3A 30VDC	0.3A 250VAC 0.3A 30VDC
Rated Carrying Current	1 A	1 A
Contact Material	Ag Alloy	Ag Alloy

8. PERFORMANCE (at initial value)

Type	SRS/SRSZ
Item	
Contact Resistance	100mΩ Max.
Operation Time	10msec Max.
Release Time	5msec Max.
Dielectric Strength	
Between coil & contact	500VAC 50/60HZ (1 minute)
Between contacts	500VAC 50/60HZ (1 minute)
Insulation Resistance	100 MΩ Min. (500VDC)
Max. ON/OFF Switching Mechanically	300 operation/min
Electrically	30 operation/min
Operating Ambient Temperature	-25°C to +70°C
Operating Humidity	45 to 85% RH
Vibration Endurance	10 to 55HZ Single Amplitude 0.35mm
Error Operation	10 to 55HZ Single Amplitude 0.35mm
Shock Endurance	50G Min.
Error Operation	10G Min.
Life Expectancy	10 ⁷ operations. Min. (no load)
Mechanically	10 ⁵ operations. Min. (at rated coil voltage)

Weight abt. 4grs.

9. REFERENCE DATA

