



YAMAHA SPEAKERS R-SERIES



R112C



R115C



R215C

Model		R112C	R115C	R215C
Type		2Way Bass reflex		
Speaker Unit	LF	12" Cone	15" Cone	15" Cone × 2
	HF	1.75" v.c.Comp. Driver		
Frequency Range		55 Hz - 20 kHz (−10 dB)	50 Hz - 20 kHz (−10 dB)	40 Hz - 20 kHz (−10 dB)
Power Capacity	NOISE*	200 W	250 W	500 W
	PGM	400 W	500 W	1000 W
	MAX	800 W	1000 W	2000 W
Nominal Impedance		8 ohms		4 ohms
Sensitivity		97 dB SPL (1W,1 m)	98 dB SPL (1W,1 m)	
Nominal Dispersion	Horizontal	90°	90°	90°
	Vertical	40°	40°	40°
Cross Over Frequency		1.7 kHz		1.5 kHz
Input Connectors		SPEAKON NL4MP × 1, 1/4" Phone Jack × 2		
Dimensions (W × H × D)		480 × 695 × 400 mm	520 × 765 × 470 mm	520 × 1175 × 600 mm
Weight		26.5 kg	35.0 kg	69.0 kg
Color		Black		
Mounting Screw		M10 3points	M10 3points	—