



AOYUE 8032A++ Hand Held Hot Gun

Turbine pump of AOYUE-8032A++ produces soft airflow, which concentrates temperature on operating components to avoid air ripple from diaphragm pump. Sensor control of temperature and airflow. Digital temperature and airflow indication. Package includes 4 nozzles.



Features:

1. Power On/Off button and airflow/temperature control buttons are located on the hot air gun handle. Reset function of parameters to be settled earlier.
2. Hot air gun is equipped with digital indicator to control temperature mode during whole operation period.
3. Discrete temperature control enables to set required temperature accurate within 1°C.
4. Automatic cooling mode (after shutdown) protects heating element.
5. Turbomotor produces soft vertical blast.
6. Antistatic performance of hot air gun enables with static-sensitive components.
7. Package includes 4 replacement nozzles (1195, 1196, 1198, 1313).
8. Hot air gun packed into cardboard box with protective frame.

Temperature range	100°C – 480°C
Temperature control	Sensor, discrete
Airflow control	Sensor, discrete
Power consumption	550 W (max.)
Operating voltage	220 V
Airflow	30 l/min.(max.)
Nozzle diameter	21,5 mm
Motor	Turbine, based on RS-365SH
Nozzles	1195, 1196, 1198, 1313
Heating element	10096
Dimensions	77 × 277 mm

Package includes:

1. Hot air gun Aoyue - 8032A++ – 1 pc.
2. Nozzles - 4 pcs.
3. User manual – 1pc.