



PABX 2/8, 3/12 and 4/16

FUZI TS series are designed to provide a family & small office with low cost professional telecom services. Max capacity is 1 to 6 CO lines & 8 to 32 Extensions.

The Auto-Attendant Service (DISA: Direct Inward System Access) with OGM (Outgoing Message service) allows the system to make the max use the CO line.

There are number of supplementary features to indicate quality of FUZI TS Series System :



- OGM (auto-attending).
- Digital Recording.
- Ringing Assignment.
- Flexible Coding.
- Six Level Call Restriction.
- Call Transferring.
- Call pickup.
- Music on holding.
- Automatic distinguishes CO Lines.
- Power Failure Transfer.
- Three Way conference.
- Intercom dialing.
- Call duration control.
- Caller ID.
- Call Forwarding.

Specifications

Capacity	CO Lines	1 to 6
	Extensions	8 to 32
Extensions		Conjunction to extension.
Communication Lines		7
Transmission Attributes		Extension To Extension $\leq 1.5\text{dB}$; Extension To trunk line $\leq 2.0\text{dB}$;
Ringing current		75v/50Hz ;
Feeding current		48v-60v/25mA
Relative unbalance against ground		300Hz - 600Hz $\geq 40\text{dB}$; 600Hz - 3400Hz $\geq 46\text{dB}$;
Dialing mode		DTMF
Signal tone	CO line	tone from local telephone company;
	Internal dialing tone	450Hz, continuous square wave;
	Extension echo signal	450Hz, square wave, 1 second on and 4 second off;
	Extension busy signal	450Hz, square wave, 0.3 second on and 0.3 second off;
	Extension confirmation signal	450Hz, square wave, 1 second on;
Power supply	AC 220V +/- 10%	
	power Consumption $\leq 15\text{VA}$	
Operational environment		Temperature : 32F-104 F(0-40) ; Relative humidity $\leq 90\%$

Made in China