



STEPPER MOTOR

(42BYG Series)

Specifications :

Pitch : 1.8 DEG

Insulation : 500V DC / 100M Ohm

Temperature : -10° C ~ 55° C

MODEL	Coil	Voltage	Curent	Impedance	Inductance	Starting torque	Wieght	Z	L
		Volt	Amp	Ohm	mH	Kg.cm	Kg	mm	mm
42BYG001	4	12	0.38	32	23	2.0	0.24	39	24
42BYG002	4	12	0.16	75	60	1.0	0.2	33	18
42BYG006	2	15.8	0.28	60	85	2.4	0.24	39	24
42BYG007	4	6	0.5	12	7	0.8	0.2	33	18
42BYG008	4	32	0.38	17	17	1.0	0.2	33	18
42BYG009	4	3.6	1.2	3	3	2.5	0.24	39	24
42BYG010	4	2.4	1.2	2	1.3	1.0	0.2	33	18
42BYG101	2	12	0.5	24	27	2.0	0.2	33	18
42BYG102	2	12	0.35	34	35	2.0	0.2	33	18
42BYG103	2	12	0.4	30	36	2.0	0.2	33	18
42BYG201	4	12	0.6	20	16	2.0	0.24	39	24
42BYG202	2	12	0.4	30	70	2.4	0.24	39	24
42BYG203	2	12	0.6	20	40	2.4	0.24	39	24
42BYG301	2	12	0.27	44	100	2.5	0.3	42	24
42BYG015	4	12	0.3	40	19	1.25	0.2	33	18
42BYG020	4	12	0.6	20	14	1.7	0.2	33	18