

STEPPER MOTOR

(57BYG Series)



Specifications : Made in Japan

Pitch : 1.8 DEG

Insulation : 500V DC / 100M Ohm

Temperature : -10° C ~ 55° C

MODEL	Coil	Voltage	Current	Impedance	Inductance	Starting torque	Torque	Weight	L
		Volt	Amp	Ohm	mH	Kg. cm	Kg. cm	Kg	mm
57BYG001	2	14	0.35	40	60	4.0	0.3	0.45	41
57BYG002	4	12	0.6	20	25	6.0	0.7	0.65	56
57BYG007	4	12	0.38	32	30	3.5	0.3	0.45	41
57BYG007-4	4	12	0.38	32	26	4.0	0.6	0.6	51
57BYG008	4	4	1.3	3.1	4.4	4.9	0.6	0.6	51
57BYG009	4	2.4	2.4	1.0	1.0	6.0	0.7	0.654	56
57BYG012	4	5.4	1.5	3.6	6.0	9.0	0.9	1.0	76
57BYG019	4	9	0.7	13	11.0	5.0	0.7	0.65	51
57BYG027	4	4	1.4	2.5	3.5	5.0	0.6	0.65	51
57BYG059	4	4	1.6	2.5	3.5	6.0	0.7	0.65	56
57BYG060	2	2.6	2.0	1.3	3.5	6.5	0.7	0.65	56
57BYG061	2	6	0.5	12	14.5	3.5	0.3	0.45	41
57BYG101	4	4	1.1	3.6	3.3	3.5	0.3	0.45	41
57BYG102	4	2.3	1.5	1.5	6.2	3.5	0.3	0.45	41
57BYG110	4	2.4	2.4	1.0	2.0	8.0	0.9	1.0	76
57BYG301	4	6	1.2	5	8.2	6.0	0.7	0.65	56
57BYG302	2	8.4	0.7	12	30	7.0	0.7	0.65	56
57BYG401	4	3.4	2.0	1.7	4.3	9.0	0.9	1.0	76
57BYG402	4	4.6	2.0	2.3	4.3	10.0	0.9	1.0	76
57BYG502	4	6.5	1.5	4.3	6.0	12.0	1.2	1.3	101
57BYG503	4	2.6	2.0	1.3	23.	12.0	1.2	1.3	101
57BYG504	4	2	4.0	0.5	0.9	12.0	1.2	1.3	101