



STEPPER MOTOR

(86BYG Series)

Specifications :

Pitch : 1.8 DEG
 Insulation : 500V DC / 100M Ohm
 Temperature : -10° C ~ 55° C

MODEL	Coil	Voltage	Curent	Impedance	Inductance	Starting torque	Torque	Wieght	Z
		Volt	Amp	Ohm	mH	Kg.cm	Kg.cm	Kg	mm
86BYG101	4	2.9	1.7	1.7	3.7	12	0.9	1.5	62
86BYG102	4	5	1.25	4	8.4	12	0.9	1.5	62
86BYG103	4	1.6	3.6	0.45	1.25	12	0.9	1.5	62
86BYG104	4	1.4	4.5	0.31	0.8	12	0.9	1.5	62
86BYG105	4	2.9	3	0.96	1.8	12	0.9	1.5	62
86BYG106	4	1.8	4.8	0.37	0.7	12	0.9	1.5	62
86BYG201	4	3	4	0.75	2.8	22	1.5	2.6	93
86BYG202	4	2.5	4.6	0.55	1.8	22	1.5	2.6	93
86BYG203	4	4.3	2.5	1.7	7.0	22	1.5	2.65	93
86BYG204	4	5.4	2	2.7	10.3	22	1.5	2.65	93
86BYG301	4	3.6	4	0.9	5.2	30	1.8	3.7	126
86BYG302	4	7.6	2	3.8	15.1	30	1.8	3.7	126
86BYG303	2	5.6	4	1.4	9.2	60	1.8	3.7	126
86BYG401	4	2	7	0.29	1.6	40	2.0	4.2	135
86BYG402	4	4	4	1.0	5.0	40	2.0	4.2	135
86BYG403	4	8.4	2	4.2	16.2	40	2.0	4.2	135
86BYG404	2	6	4	1.5	10.5	70	2.0	4.2	135