

4nF $\pm(5\%+40d)$,

PROSKIT MT-1506 POCKET



PROSKIT MT-1506 POCKET TRUE-RMS AUTO RANGE MULTIMETER

- Comply with CE EN61010-1 CATII 600V Safety rated
- 3-3/4 digits 3999 counts
- 0.5% best accuracy
- Both auto and manual range provide accurate measurement
- ACV True RMS measurement
- Overload protection circuit design
- Auto power off for energy saving
- Pocket size design for easy carrying
- Now Built-in test lead
- Extra function: Continuity with beeper, Hz/Duty, Auto
- power off, low batter indication

Specifications:	MT-1506
DCV:	400mV,4/40/400V $\pm(0.5\%+4d)$, 600V $\pm(1\%+4d)$
ACV:	400mV $\pm(1.5\%+6d)$, 4/40/400V $\pm(0.8\%+6d)$, 600V $\pm(1.0\%+6d)$
Resistance:	400 Ω $\pm(0.8\%+5d)$ 4k/40k/400k/4M Ω $\pm(0.8\%+4d)$, 40M Ω $\pm(1.2\%+5d)$
Frequency:	100/1000Hz/10k/100k/1MHz/10MHz $\pm(0.5\%+4d)$ 4nF $\pm(5\%+40d)$,
Capacitance:	40n/400n/4 μ /40 μ $\pm(3.5\%+8d)$, 2000 μ F $\pm(5\%+8d)$
Duty cycle:	0.1~99.9% $\pm(0.5\%+4d)$
Continuity with beeper:	50 $\pm 30\Omega$
Diode test:	Range: 0 ~ 1.5V Resolution: 1mV
Power source:	2 x 1.5V AAA battery (Not included)
Size:	4.9 x 3.1 x 0.8"
Individual packing:	Color box

